



Optional

JIT-01
Trolley



Technical Data

Input Voltage	95-265V - AC 50/60Hz	
	115V	230V
I _{eff} (A)	20.1	14.8
Input Power (kVA)	4.2	5.8
Voltage Adjustment Range (V)	11 - 28	
Current Range (A)	MIG 30 - 140	30 - 200
	MMA 10 - 140	10 - 180
Duty Cycle @ 40°C	200A @ 35%	
No-Load Voltage (V)	53	
Wire Spool Size	ø 200mm	
Efficiency (%)	85	
Power Factor	0.10	
Protection/Insulation Class	IP21S/F	
Dimensions (LxWxH mm)	485 x 185 x 370	
Weight (Kg)	12.8	

Key Features

- IGBT MIG/MMA Multi Process Inverter technology - for the professional user
- Wide input voltage 95-265V
- PFC - Energy saving benefits for the user
- Single PCB compact welding inverter
- Stable arc and reliable performance
- Suitable for 0.6 to 1.0mm wires
- Compact size, lightweight and modern design
- Burn back control
- Ideal for production, site work & maintenance
- Reverse polarity
- Can weld electrodes of up to 4mm
- Generator friendly**



Package Includes

Inverter power source, MIG welding torch, Work return lead and clamp, Gas hose and regulator, Operating instructions, 5 year warranty*



* 5 year warranty subject to product registration **Generators should have regulated output